



US005645011A

United States Patent [19]

Winkler et al.

[11] Patent Number: **5,645,011**

[45] Date of Patent: **Jul. 8, 1997**

[54] **FLUID FLOW INDICATOR**

[75] Inventors: **Bruce Winkler; Rocky Van Asten,**
both of Madison, Wis.

[73] Assignee: **PDQ Food Stores, Inc.,** Middleton,
Wis.

[21] Appl. No.: **282,531**

[22] Filed: **Jul. 28, 1994**

[51] Int. Cl.⁶ **G01F 15/00; B01D 35/00**

[52] U.S. Cl. **116/264; 116/273; 73/323;**
73/325; 210/416.4

[58] Field of Search **116/271, 272,**
116/273, 274, 276, 264; 73/323, 325, 326,
328, 329, 330, 334; 141/94; 137/559, 550;
210/94, 448, 452, 416.4, 497.1

[56] **References Cited**

U.S. PATENT DOCUMENTS

1,032,766	7/1912	Paul .	
1,076,128	10/1913	Kupferle	210/448
1,110,974	9/1914	Van Buskirk et al.	73/326
1,239,304	9/1917	Pocock	73/326
1,638,066	8/1927	Smythe	210/94
1,673,000	6/1928	Fagan .	
1,730,118	10/1929	Cobb .	
1,783,379	12/1930	Jacob .	
1,865,002	6/1932	Griffin .	
1,904,283	4/1933	Fagan et al. .	
1,971,120	8/1934	Rice et al.	210/448
2,097,535	11/1937	Rugel et al. .	
3,080,972	3/1963	Smith .	
3,272,337	9/1966	Elwell	210/448
3,317,043	5/1967	Vanderpool	210/94
3,458,050	7/1969	Cooper	210/448

4,345,468	8/1982	Jackson .	
4,745,877	5/1988	Chang .	
4,819,577	4/1989	Campau .	
4,993,460	2/1991	Robinson et al. .	
5,097,866	3/1992	Shapiro-Baruch et al.	137/550
5,125,269	6/1992	Horst, Jr. .	
5,244,017	9/1993	Hartman et al. .	
5,249,707	10/1993	Simpson et al. .	
5,368,648	11/1994	Sekizuka	277/3

FOREIGN PATENT DOCUMENTS

B1-37 981/78	12/1978	Australia .
514360	3/1921	France .
2677971	6/1991	France .
1244517	9/1971	United Kingdom .

OTHER PUBLICATIONS

OPW® Engineered Systems promotional material for
VISI-FLO® Sight Flow Indicators.

Primary Examiner—William A. Cuchlinski, Jr.

Assistant Examiner—Andrew Hirshfeld

Attorney, Agent, or Firm—DeWitt Ross & Stevens SC

[57] **ABSTRACT**

A fluid flow indicator is presented particularly for use within an existing gasoline pumping apparatus. The fluid flow indicator includes an outer cage member, a first hollow transparent cylindrical member contained within the outer cage member, and a second hollow transparent cylindrical member concentrically retained within the first hollow transparent cylindrical member. The fluid flow indicator may also include a filter member and fluid movement detection means contained within the second hollow transparent cylindrical member. The fluid flow indicator is especially designed to be retrofitted within any existing fluid flow line.

7 Claims, 3 Drawing Sheets

